

Tubi® Overview



Tubi® Technical

Sophisticated simplicity, the Tubi will complement any interior. Its elegant Italian designed 38mm vertical tubes are exquisitely arranged either side of a horizontal bar to provide a subtle symmetry that belies a good heat output.

Features

- Material - Steel
- Finish - RAL 9016 Traffic White
Other colours available on request
- Heights - 330-2030mm
- Widths - 318-1662mm
- Sizes - 365
- Outputs - 267-3498 watts
- Maximum Working Pressure - 8 bar (10 bar test)
- Warranty - 5 years



Technical data per tube

	Height (mm)																
	330	380	430	474	530	574	630	724	780	830	874	930	1030	1774	1830	1974	2030
Dry weight per tube (kg)	0.84	0.95	1.06	1.13	1.27	1.35	1.49	1.67	1.82	1.93	2.00	2.15	2.36	3.96	4.11	4.40	4.54
Water content per tube (litres)	0.72	0.82	0.92	1.01	1.12	1.21	1.32	1.51	1.62	1.72	1.81	1.92	2.12	3.60	3.71	4.00	4.11

Performance data

Performance data		Height (mm)																
		330	380	430	474	530	574	630	724	780	830	874	930	1030	1774	1830	1974	2030
Width (mm)	Tubes	Output (watts Δt 50°C)																
318	6	267	301	333	361	397	424	458	516	550	580	607	640	700	1140	1173	1259	1293
374	7	312	351	389	421	463	495	535	602	642	677	708	747	816	1330	1369	1469	1509
430	8	356	401	444	482	529	566	611	688	734	774	809	854	933	1520	1564	1679	1724
486	9	401	451	500	542	595	636	688	774	825	870	910	960	1049	1710	1760	1889	1940
542	10	445	501	555	602	661	707	764	860	917	967	1011	1067	1166	1900	1955	2099	2155
598	11	490	551	611	662	727	778	840	946	1009	1064	1112	1174	1283	2090	2151	2309	2371
654	12	534	601	666	722	793	848	917	1032	1100	1160	1213	1280	1399	2280	2346	2519	2586
710	13	579	651	722	783	859	919	993	1118	1192	1257	1314	1387	1516	2470	2542	2729	2802
766	14	623	701	777	843	925	990	1070	1204	1284	1354	1415	1494	1632	2660	2737	2939	3017
822	15	668	752	833	903	992	1061	1146	1290	1376	1451	1517	1601	1749	2850	2933	3149	3233
878	16	712	802	888	963	1058	1131	1222	1376	1467	1547	1618	1707	1866	-	-	-	-
934	17	757	852	944	1023	1124	1202	1299	1462	1559	1644	1719	1814	1982	-	-	-	-
990	18	801	902	999	1084	1190	1273	1375	1548	1651	1741	1820	1921	2099	-	-	-	-
1046	19	846	952	1055	1144	1256	1343	1452	1634	1742	1837	1921	2027	2215	-	-	-	-
1102	20	890	1002	1110	1204	1322	1414	1528	1720	1834	1934	2022	2134	2332	-	-	-	-
1158	21	935	1052	1166	1264	1388	1485	1604	1806	1926	2031	2123	2241	2449	-	-	-	-
1214	22	979	1102	1221	1324	1454	1555	1681	1892	2017	2127	2224	2347	2565	-	-	-	-
1270	23	1024	1152	1277	1385	1520	1626	1757	1978	2109	2224	2325	2454	2682	-	-	-	-
1326	24	1068	1202	1332	1445	1586	1697	1834	2064	2201	2321	2426	2561	2798	-	-	-	-
1382	25	1113	1253	1388	1505	1653	1768	1910	2150	2293	2418	2528	2668	2915	-	-	-	-
1438	26	1157	1303	1443	1565	1719	1838	1986	2236	2384	2514	2629	2774	3032	-	-	-	-
1494	27	1202	1353	1499	1625	1785	1909	2063	2322	2476	2611	2730	2881	3148	-	-	-	-
1550	28	1246	1403	1554	1686	1851	1980	2139	2408	2568	2708	2831	2988	3265	-	-	-	-
1606	29	1291	1453	1610	1746	1917	2050	2216	2494	2659	2804	2932	3094	3381	-	-	-	-
1662	30	1335	1503	1665	1806	1983	2121	2292	2580	2751	2901	3033	3201	3498	-	-	-	-

For Δt 30°C, apply a correction factor of 0.515. For other operating temperatures, refer to page 131.

