

Decoral 77

Declaration of Performance



DOP No.	2608-36	Unique Product Code	DEC77
Trading Name	Decoral 77	Type, Batch, or Serial Number	DEC77-_-_-_-

Manufacturer:

MHS Radiators Ltd, Unit 4 Genesis, Endeavour Drive, Basildon, SS14 3WF

Tel: 0345 521 5666 | Email: mhs@modularhg.co.uk | Website: www.mhsradiators.co.uk

System of ACVP:

System 3

Declared uses of the product, within the scope of the applicable harmonised technical specification:

Aluminium radiator fed with water or steam, suitable for operation at temperatures below 120°C.

Notified Laboratory:

Laboratorio M.R.T. - Notified Body Number: 1695

Via Raffaele Lambruschini 4A, 20156 Milano

Tel: 02-23993825 | E-mail: mrt@polimi.it | Website: www.mrt.polimi.it

Harmonised technical specifications:

EN 442-1:2014

Decoral 77

Declaration of Performance



Declared performance:

Performance of the essential characteristics defined by the harmonised technical specification:

Essential Characteristics	Performance				
Fire reaction	A1				
Release of dangerous substances	NO				
Maximum working pressure	16 bar				
Pressure tightness	Pass (24 bar)				
Pressure resistance	Pass (32 bar)				
Maximum surface temperature	120°C				
Rated thermal output (per section)	Height mm	Output ΔT 50°C watts	Output ΔT 30°C watts	K_m	n
	500	98.8	51.3	0.6524	1.2833
	600	113.5	58.6	0.7203	1.2935
	700	130.4	67.2	0.8088	1.2993
Characteristic curve	$\Phi = K_m \times \Delta T^n$				
Resistance against corrosion	No > 200h				
Resistance against minor impact	Class 0				

Signed for and on behalf of the manufacturer by:

Alex Bradley
Commercial Director
18/09/26